

Specifications		FX-7
LCD	Size	7"
	Resolution	1920 x 1200 (16:10)
	Pixel Pitch	0.07875(H) x 0.07875(V) mm
	Color Depth	1.073B Colors
	Viewing Angle	160°(H) / 160°(V)
	Luminance of white	2000cd/m2
	Contrast Ratio	1200 : 1
	Display Area	151.2(H) x 94.5(V) mm
Video Input	2 x BNC	1 x 12G/6G/3G/HD-SDI Input
	1 x HDMI	Up to UHD 4K(4096x2160/60p) Input
Video Output	1 x BNC	12G/6G/3G/HD-SDI A/B Selectable Output (LUT Applied Out, HDMI to SDI Conversion Out)
	1 x HDMI	HDMI Output
Input Signal	12G-SDI	12Gb/s
	6G-SDI	6Gb/s
	3G-SDI	2.970Gb/s
	HD-SDI	1.485Gb/s
	HDMI	480i / 480p / 576i / 576p / 720p / 1080i / 1080p / 2160p
SDI Input Signal Formats	SMPTE ST 2082	3840x2160 (60/50/30/25/24p)
	SMPTE ST 2081	3840x2160 (30/25/24p)
	SMPTE ST 2036-1	3840x2160 (23.98/24/25/29.97/30/50/59.94/60p)
	SMPTE ST-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-260M	1035i (60/59.94)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
SMPTE ST 2048-2	2048x1080 (23.98/24/25/29.97/30p/psf, 47.95/48/50/59.94/60p)	
Audio	Audio Input	SDI Embedded Audio (Group, Ch Selectable)
	Audio Output	External Output Port (3.5mm Phone Jack)
Power Input	1 x LEMO 2pin	DC 12V
	1 x USB-C PD	Min. 45W
Power Output	1 x LEMO 2pin	DC Pass-through Out
Update	1 x USB	USB-C type, Firmware Upgrade
Power Consumption (Approx.)		TBD
Operating Temperature		0°C to 40°C (32°F to 104°F)
Storage Temperature		-20°C to 60°C (-4°F to 140°F)
Dimensions	Main Body	210 x 131 x 45.9 (mm) / 8.26 x 5.15 x 1.80 (inch)
	Shipping Box	TBD
Weight		TBD
Accessories	Standard	D-Tap-C Cable
	Optional	V-Mount Battery Bracket, Anton-Bauer(Gold) Battery Bracket, Carrying Case, AC-DC Adapter, Sun Hood

*The specifications above may be changed without notice.