

Specifications		LVM-096A
LCD	Size	10.1"
	Resolution	1920x1200 (16:10)
	Pixel Pitch	0.1122(H) x 0.1128(V) mm
	Color Depth	16.7M Colors
	Viewing Angle	170°(H) / 170°(V)
	Luminance of white	1000 cd/m ²
	Contrast Ratio	1000 : 1
	Display Area	216.58(H) x 135.36(V) mm
Input Connector	1 X HDMI	HDMI Input
	1 X BNC	SDI A Channel Input
	1 X BNC	SDI B Channel Input, CVBS Channel Input (shared)
Output	1 X BNC	SDI Channel Output (Active Loop Through)
Input Signal	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270Mbps
	HDMI	1080p (60)/1080i(60)/720p(60)/480i(60)/480p(60)/576i(50)/576p(50) 640x480/720x400/800x600/1024x768/ 1280x768/1280x1024/1366x768
	Analog	CVBS (SDI B Channel)
Analog Input Spec	CVBS	1.0Vpp (with Sync)
SDI Input Signal Formats	SMPTE-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i (60/59.94/50)
	SMPTE-274M	1080p (30/29.97/25/24/24sF/23.98/23.98sF/ 50/59.94/60)
		1080i (60/59.94/50)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-260M	1035i (60/59.94)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
	2K Format	2048 x 1080p (24/24sF/23.98/23.98sF)
Audio In		Embedded Audio / Analog Stereo (Phone Jack)
Audio Out		Analog Stereo (Phone Jack), Internal speaker (Mixed Mono)
Power		DC 12/24V (XLR-4pin (male) connector)
Power Consumption (Approx.)		30 Watts(DC)/Max 2A
Operating Temperature		0°C to 40°C (32°F to 104°F)
Storage Temperature		-20 °C to 60 °C (-4 °F to 140 °F)
Main Body Dimensions		254.0 X 175.0 X 60.0(mm) / 10.00 X 6.89 X 2.36(inch)
Main Body Dimensions with stand		295.2 X 194.2 X 90.0(mm) / 11.62 X 7.65 X 3.54(inch)
Shipping Box Dimensions		330.0 X 180.0 X 250.0(mm) / 12.99 X 7.09 X 9.84(inch)
Weight		2.40kg / 5.29 lbs
Basic Accessories		AC Power Cord, DC Power adaptor, Stand, Tap Bolt
Optional Accessories		Acrylic Protector, Sun Hood