

Specifications		LVM-181S
LCD	Size	18.5"
	Resolution	1920 x 1080 (16:9)
	Pixel Pitch	213(per one triad) x 213 [um]
	Support Color	1.06B Colors
	Luminance of white	500cd/m2 (Typical)
	Contrast Ratio	1000 (Typical)
	Active Area	408.96(H) x 230.04 (V) [mm]
Input Connector	2 X BNC	SDI A/B Channel Input
	3 X BNC	Analog Input
	1 X HDMI	HDMI Input
	1 X DVI-I	DVI-I(RGB) IN
Output	2 X BNC	SDI A/B Channel (Loop Through Out)
	3 X BNC	Analog Output
Input Signal	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	Analog	CVBS / Component / RGB
	DVI-Analog	640x480/720x400/800x600/1024x768/1366x768
	DVI-D (PC mode)	640x480/800x600/1024x768/1366x768
	DVI-D (HDMI mode)	1080i(60) / 720i(60) / 480i(60) / 480p(50)
	HDMI	480i(60) / 480p(60) / 576i(50) / 576p(50) / 720p(60) / 1080i(60) / 1080p(60)
Analog Input Spec	CVBS	1.0Vpp (with Sync)
	Component	1.0Vpp (Y with Sync), 0.7Vpp (Pb,Pr)
	RGB	1.0Vpp (G With Sync), 0.7Vpp (B,R)
SDI Input Signal Formats	SMPTE-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i (60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50), 1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-260M	1035i (60/59.94)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
	2K Format	2048 x 1080(23.98p/psf, 24p/psf)
Audio	Audio In	Embedded Audio / Analog Stereo (Phone Jack)
	Audio Out	Analog Stereo (Phone Jack), Internal Speaker(Stereo)
Power		AC100~240V(50~60Hz) / DC 12V
Power Consumption (Approx.)		30 Watts
Operating Temperature		0°C to 40°C (32°F to 104°F)
Storage Temperature		-20°C to 60°C (-4°F to 140°F)
Dimensions	Main Body (mm/inch)	442.5 x 309 x 70 (mm) / 17.42 x 12.17 x 2.76 (inch)
	With stand (mm/inch)	489.7 x 332.8 x 137.5 (mm) / 19.28 x 13.1 x 5.41 (inch)
Weight		7Kg / 15.43 lbs
Accessory	Basic	AC Power Cord, Stand, USB Cover, Control Knob Cap
	Optional	Sun Hood, Acrylic Filter, Rack Mount Kit, Carrying Case, V-Mount, G-Mount