

R-9D

LCD	Size	10.1"
	Resolution	1920 x 1200 (16:10)
	Pixel Pitch	0.1128(H) x 0.1128(V) mm
	Color Depth	16.7M Colors (8 bit)
	Viewing Angle (Typ.)	170°(H) / 170°(V)
	Luminance of white	800cd/m2
	Contrast Ratio	1000 : 1
	Display Area	216.58(H) x 135.36(V) mm
Input	1 X HDMI	HDMI Input
	1 X BNC	3G-SDI
	1 X BNC	12G-SDI
	2 X RJ45	RS-422, REMOTE
Output	1 X BNC	12G-SDI OUT (Passive Through Out)
	1 X BNC	3G-SDI OUT (Passive Through Out)
	1 X RJ45	RS-422
Input Signal	12G-SDI	11.88Gb/s
	6G-SDI	5.94Gb/s
	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	HDMI	1080p(60/59.94/50/30/25/24/23.98)/ 1080i(60/59.94/50)/720p(60/50)/480i(60)/480p(60)/576i(50)/576p(50)
SDI Input Signal Formats	SMPTE ST 2082	2160p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 2160i (60/59.94/50)
	SMPTE-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i (60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p(60/59.94.50/30/29.97/25/24/23.98)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
Audio In		Embedded Audio
Audio Out		Speaker
Power		DC 12V / 3.4A
Power Consumption (Approx.)		38W
Operating Temperature		0°C to 40°C (32°F to 104°F)
Storage Temperature		-20°C to 60°C (-4°F to 140°F)
Main Body Dimensions		481.0 x 175.8 x 60.5(mm) / 18.93 x 6.92 x 2.38(inch)
Main Body Dimensions with RMK		481.0 x 175.8 x 88.0(mm) / 18.93 x 6.92 x 3.46(inch)
Box Dimensions (mm/inch)		555.0 x 230.0 x 165.0(mm) / 21.85 x 9.06 x 6.50(inch)
Weight		2.95Kg / 6.50lbs
Basic Accessories		AC Power Cord, DC Power Adapter, Rack Mount Kit(Body)
Optional Accessories		-

*The specifications above may be changed without notice.