

Specifications		LVM-242S
LCD	Size	24"
	Resolution	1920 x 1200 (16:10)
	Pixel Pitch	0.270 x 0.270 mm
	Support Color	1.07B Colors (10 bit)
	Luminance of white	400cd/m2
	Contrast Ratio	1800 : 1
	Active Area	518.4(H) x 324.0(V) mm
Input	2 x BNC	SDI A/B Channel Input
	3 x BNC	Analog Input
	1 x HDMI	HDMI Input
	1 x DVI-I	DVI-I(RGB) IN
Output	2 x BNC	SDI A/B Channel (Loop Through Out)
	3 x BNC	Analog Output
Input Signal	3G-SDI	2.970Gb/s
	HD-SDI	1.485Gb/s
	SD-SDI	270 Mb/s
	Analog	CVBS / Component / RGB
	DVI-Analog	640x480/720x400/800x600/1024x768/1366x768
	DVI-D (PC mode)	640x480/800x600/1024x768/1366x768
	DVI-D (HDMI mode)	1080i(60) / 720i(60) / 480i(60) / 480p(50)
	HDMI	480i(60) / 480p(60) / 576i(50) / 576p(50) / 720p(60) / 1080i(60) / 1080p(60)
Analog Input Spec	CVBS	1.0Vpp (with Sync)
	Component	1.0Vpp (Y with Sync), 0.7Vpp (Pb,Pr)
	RGB	1.0Vpp (G With Sync), 0.7Vpp (B,R)
SDI Input Signal Formats	SMPTE-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50), 1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-260M	1035i (60/59.94)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
2K Format	2048 x 1080(23.98p/psf, 24p/psf)	
Remote Control & Update	1 x LAN	RJ-45 Input, Control by TVLogic Protocol
	1 x REMOTE	RJ-45 Input, GPI Control
	2 x RS-422	RJ-45 Input & Output, Control by TVLogic Protocol
	1 x USB	USB A type, Firmware Upgrade
Audio In		Embedded Audio / Analog Stereo (Phone Jack)
Audio Out		Analog Stereo (Phone Jack), Internal Speaker(Stereo)
Power		DC 12~24V / AC100~240V(50~60Hz)
Power Consumption (Approx.)		TBD
Operating Temperature		0°C to 40°C (32°F to 104°F)
Storage Temperature		-20°C to 60°C (-4°F to 140°F)
Dimensions	Main Body	552.5 x 389 x 98.5 (mm) / 21.85 x 15.31 x 3.87 (inch)
	With Stand	586 x 417 x 150 mm (23.07 x 16.41 x 5.90 inch)
	Shipping Box	675 x 535 x 280 mm (26.57 x 21.06 x 11.02 inch)
Weight (with stand)		10.68kg / 23.54lbs
Basic Accessories		AC Power Cord, Stand
Optional Accessories		Acrylic Filter, V-mount, G-mount, Carrying Case, Rack Mount Kit

*The specifications above may be changed without notice.