

Specifications		R-7D
LCD	Size	7.02"
	Resolution	1920×1200
	Pixel Pitch	0.07875(W) x 0.07875(H) mm
	Color Depth	16.7M (True)
	Viewing Angle (Typ.)	160°(H)/160°(V)
	Luminance of white	500 cd/ m <sup>2</sup> (Center)
	Contrast Ratio	1,200 : 1
	Display Area	151.2(H)x94.5(V) mm
Input	1 X HDMI	HDMI Input
	1 X BNC	3G-SDI
	1 X BNC	12G-SDI
	2 X RJ45	RS-422, REMOTE
Output	1 X BNC	12G-SDI OUT (Passive Through Out)
	1 X BNC	3G-SDI OUT (Passive Through Out)
	1 X RJ45	RS-422
Input Signal	12G-SDI	11.88Gb/s
	6G-SDI	5.94Gb/s
	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	HDMI	1080p(60/59.94/50/30/25/24/23.98)/ 1080i(60/59.94/50)/720p(60/50)/480i(60)/480p(60)/576i(50)/576p(50)
SDI Input Signal Formats	SMPTE ST 2082	2160p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 2160i (60/59.94/50)
	SMPTE-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i (60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p(60/59.94.50/30/29.97/25/24/23.98)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
Audio In	Embedded Audio	
Audio Out	Speaker	
Power	DC 12V / 1.85A	
Power Consumption (Approx.)	22W	
Operating Temperature	0°C to 45°C (32°F to 113°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Main Body Dimensions (mm/inch)	430 X 120 X 50.5 (16.93 X 4.72 X 1.99)	
Main Body Dimensions with RMK (mm/inch)	480.8 X 132 X 73 (18.92 X 5.19 X 2.87)	
Box Dimensions (mm/inch)	555 X 165 X 230 (21.85 X 6.50 X 9.06)	
Weight	2.46Kg / 5.42lbs	
Basic Accessories	DC Power adapter, Rack Mountable Kit	
Optional Accessories	-	

\* The specification above may be changed without notice.

\* When using a DC Adapter other than the one supplied by the manufacturer, please be advised that the adapter with DC 12V/3A ~ 6A can be compatible with the monitor.